

SURE FLAME

Model S1505B

Direct Fired Heater

Component upgrades virtually eliminate electrical service calls

- CSA Certified
- Efficient motor reduces amp draw (9.4 amp) and is rated to run on standard 15 amp circuit
- Remote (15' long) thermostat with Hi/Lo/Off control
- Relays pull in and hold tight down to 50V
- Upgraded heater control board . . .
 - starts heater with low voltage down to 95V
 - built-in diagnostics
 - runs stable when voltage drops down to 83V
 - potted control board minimizes moisture and vibration
 - rated to -40°F
- Quick changeover from propane to natural gas with a turn of a ball valve
- Tough sturdy frame allows easy stacking and saves storage space
- Lifting loop and carry bars makes moving simple



sold exclusively by
heat wagon

SPECIFICATIONS

Input	1,500,000 - 850,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	16.4 GPH Propane/1500 CFH NG
Gas Connection	1 1/4" FNPT
Electrical	120 Volts 15 amp circuit
Fan	7000 CFM 1 HP
Thermostat	2 Stage Hi/Lo/Off w/15'Remote
Temp Rise	490°F
Shipping Dim.	69"L x 32"W x 41.5"H
Approx. Weight	300 lbs.

Gas Supply:	Inlet Pressure	
	Max W.C.	Min W.C.
Propane	14"	9"
Natural	14"	9"

(Minimum inlet pressure is for purpose of input adjustment)
Recommend 11SV08 gas regulator