

# TRADESMAN®

## FORCED AIR LP/NG HEATERS

FUEL TYPE(S) AVAILABLE: LP, NG, & DUAL FUEL

Engineered to deliver reliable, directional heat, the Tradesman® heaters feature a unique 3-trial ignition system, the industry's heaviest gauge combustion chamber and burner plate, and Self Diagnostic Service Saver models for convenient trouble-shooting.



Variable output control for maximum fuel efficiency



Industry's heaviest gauge combustion chamber and burner plate for longest life



Ultra Models include illuminated diagnostic light for convenient troubleshooting

TRADESMAN®	125	170	170 ULTRA	170N	170N ULTRA	400	400 ULTRA	400 ULTRA DF
BTU/H RATING	70,000-125,000	125,000-170,000	125,000-170,000	125,000-155,000	125,000-155,000	250,000-400,000	250,000-400,000	170,000-400,000*
HEATED AIR OUTPUT (CFM)	400	550	550	550	550	1,050	1,050	1,050
FUEL TYPE	LP	LP	LP	NG	NG	LP	LP	LP/NG
FUEL CONSUMPTION LP GAS MAX. (LBS./HR.)	3.3 / 5.8	5.8 / 7.8	5.8 / 7.8	-	-	11.6 / 18.5	11.6 / 18.5	11.6 / 18.5
FUEL CONSUMPTION NAT. GAS MAX. (CU.FT./HR.)	-	-	-	125 / 155	125 / 155	-	-	250 / 400
AMPS (STARTING/CONTINUOUS OPERATION)	2.0 / 0.70	3.7 / 2.1	3.7 / 2.1	3.7 / 2.1	3.7 / 2.1	4.0 / 1.5	4.0 / 1.5	4.0 / 1.5
SERVICE SAVER (SELF-DIAGNOSTICS)	-	-	YES	-	YES	-	YES	YES
LENGTH (IN.)	25.6	24.0	24.0	24.0	24.0	34.5	34.5	34.5
WIDTH (IN.)	11.8	9.5	9.5	9.5	9.5	12.5	12.5	12.5
HEIGHT (IN.)	16.0	16.0	16.0	16.0	16.0	21.5	21.5	21.5
SHIPPING WEIGHT (LBS.)	28.0	34.0	34.0	34.0	34.0	51.0	51.0	55.0

\*250,000 - 400,000 BTU/H on LP.

- Thermostatic temperature control (170 and 400 models)
- Variable heat output promotes fuel savings
- Dependable electronic spark ignition

- Tri-Shield finish protects against abrasion and corrosion.
- Adjustable front leg to direct heat (125 and 170 model)
- CSA certified for US and Canada (400 Ultra DF CSA cert. US only)