

# Phoenix R200 LGR Dehumidifier

## Specifications

<b>Part No.</b>	4027000
<b>Power</b>	8.3 amps, 120 VAC, Grounded
<b>Water Removal</b>	125 pints/day @ AHAM (80 °F, 60%) 26 gal/day maximum @ saturation
<b>Blower</b>	325 CFM without external ducting 300 CFM @ .15 IWG external static
<b>Refrigerant Charge</b>	1 lb, 10 oz. R-410A
<b>Operating Range</b>	33 °F to 110 °F
<b>Filters:</b>	12" x 12" x 1" Pleated Media MERV-11
<b>Duct Options</b>	Intake - 12" Flex-Duct Outlet - 10" Lay-Flat
<b>Warranty</b>	Five years; 1st year 100% of Parts and Labor 2nd-5th year 100% of sealed refrigeration system parts.

## Dimensions

	Unit	Shipping
Width	20"	21"
Height	33.5"	35.25"
Depth	20"	21"
Weight	105 lbs	115 lbs

Like every Phoenix, the R200 features effective air filtration with a pleated media MERV-11 filter. Multiple ducting options are available with 12" intake duct tabs on the lid and a wire duct collar for 10" lay-flat duct on the exhaust.



Intertek  
Xactimate Code:  
WTRDHM>>

Patented  
**BYPASS**<sup>TM</sup>  
TECHNOLOGY

## Features

- Removes 125 pints per day at AHAM (80°F/60% RH)
- Patented bypass technology
- Draws only 8.3 amps and removes 5.2 pints/kWh
- Overall dimensions 20" x 20" x 33.5"
- Weighs 105 lbs
- 325 CFM; faster drying and superior static pressure for ducting
- Multiple ducting options - 12" intake, 10" exhaust
- Solid state controls
- R-410A Refrigerant
- Protected condensate hose
- Telescoping handle
- Recessed 12" Wheels
- Pleated 12" x 12" x 1" MERV-11 media air filter
- Stacks easily reducing storage space
- Rugged roto-molded housing

Made in USA

[www.UsePhoenix.com](http://www.UsePhoenix.com)

innovative

DESIGN

exceptional

VALUE

proven™

PERFORMANCE