

NEW & ENHANCED **PREMIER® 350 DF 2.0**
Enclosed Flame Portable Heater

| PREMIER® | 350 DF 2.0 |
|--|---------------------------|
| BTU/H RATING | 350,000 |
| HEATED AIR OUTPUT (CFM) | 2,500 |
| FUEL TYPE | LP, NG |
| FUEL CONSUMPTION LP GAS MAX (LBS./HR.) | 16.2 |
| FUEL CONSUMPTION NAT. GAS MAX (CU.FT./HR.) | 350 |
| AMPS (STARTING/CONTINUOUS OPERATION) | 25.0 / 9.0 |
| AMPS (STANDARD 15 AMP CIRCUIT) | YES* |
| ELECTRICAL CONNECTION MOUNTED INLET | YES |
| MOTOR HORSEPOWER | 1 |
| RUNNING DECIBELS | 72 |
| LENGTH (IN.) | 48.3 |
| WIDTH (IN.) | 28.0 |
| HEIGHT (IN.) | 41.0 |
| SHIPPING WEIGHT (LBS.) | 320.0 |
| FAN ONLY MODE | S |
| TRI-SHIELD COATED CASE** | S |
| WHEELS | S |
| GAS PRESSURE REGULATOR (W/POL) | S |
| THERMOSTAT CONNECTION MOUNTED INLET | YES |
| THERMOSTAT (WEATHERPROOF W/ 1.4' CORD) | S |
| GAS HOSE | 15' |
| DUCTING (W/ MAGNETIC DUCT ADAPTER)*** | 18" DIA. X 12" LONG-24442 |
| LINK™ READY | S |
| CERTIFIED TO ANSI/CSA STANDARDS | YES |

TWO YEAR WARRANTY



S=Standard

*Amps spike over 15 during initial start-up. Check breaker capability

** Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

*** Ducts are optional. Part numbers listed. Duct part numbers can differ for previously built models. Please call L.B. White for specific part numbers.


CA RESIDENTS:



Cancer and reproductive harm. See www.P65Warnings.ca.gov.

Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

INNOVATIVE HEATING SOLUTIONS



© 2021 L.B. White Co.
 All rights reserved.
 All specifications are subject to change without notice.