

TECHNICAL SPECS		OFFICE PRO [™] 60*
Electronic Features	Control	Programmable
Cooling Capacity	Rating Conditions: 95°F at 60% RH	60,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 208/230V 6.6 kW 29 amps 50 amps 6 - 50 198 - 250
Fans	Motor Output - high/low	0.5/0.33 kW (Evaporator) 1.2/0.93 kW (Condenser)
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 1940/1770 CFM 0.9 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 2830/2650 CFM 0.85 IWG
Compressor	Type Output	Hermetic Scroll 3.9 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	30 x 52 x 64 in
Net Weight/Shipping Weight		623/732 lb
Power Cord	Gauge/Length	6 AWG (3-core)/6 ft
Condensate Tank Capacity		Auto Pump Included
Operating Conditions	Min. – Max. (@ 50% RH)	65° - 105°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	40 ft 100 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	69/67 dB(A) 71/69 dB(A)

* Specification information shown with 230V

All specifications subject to change without notice.