

INDIRECT FIRED HEATERS



FVO-400



FVO-400RC



FVNP-400



FVNP-400RC

MODEL	FVO-400	FVO-400RC	FVNP-400	FVNP-400RC
FUEL TYPE	OIL	OIL	DUAL FUEL - LP/NG	DUAL FUEL - LP/NG
BTU/HR	390,000	390,000	390,000	390,000
CFM	2,500 (DUCT UP TO 50')	4,000 (DUCT UP TO 150')	2,500 (DUCT UP TO 50')	4,000 (DUCT UP TO 150')
POWER REQUIREMENTS	115V/15A	115V/15A	115V/15A	115V/15A
FUEL TANK CAPACITY* RUN TIME* FUEL CONSUMPTION*	42 GALLONS 14HRS 2.75 GAL/HR	42 GALLONS 14HRS 2.75 GAL/HR	EXTERNAL	EXTERNAL
HEAT EXCHANGER	16 GAUGE 304 SS	16 GAUGE 304 SS	16 GAUGE 304 SS	16 GAUGE 304 SS
AIR OUTLET DIA.	(2) 12", (1) x 16", OR (1) x 20"	(2) 12", (1) x 16", OR (1) x 20"	(2) 12", (1) x 16", OR (1) x 20"	(2) 12", (1) x 16", OR (1) x 20"
AIR INLET DIA.	-	(1) x 16"	-	(1) x 16"
BURNER TECHNOLOGY	RIELLO BURNER	RIELLO BURNER	RIELLO BURNER	RIELLO BURNER
RETURN AIR	NO	YES	NO	YES
L x W x H	70" x 29" x 52"	70" x 29" x 54"	70" x 29" x 47"	70" x 29" x 54"
WEIGHT	450 LBS	450 LBS	365 LBS	365 LBS

*BASED ON 100% INPUT CAPACITY.

FEATURES

Enhanced Technology

Proven Riello burner technology including nozzle pre-heater for cold weather start up and upgraded low temperature fuel pump.

Extended Duct Runs

FVO-400RC and FVNP-400RC models feature a powerful backward incline blower that provides ultra-quiet operation and low amperage.

Manufactured With Durable Materials

16-inch high density flat free wheels, smart power indicator control, volt meter, and stainless steel heat exchanger.

Optional Add-Ons

Tiger-loop fuel filter system that eliminates fuel system air locks and 118 gallon fuel tank available.

