



Classic 10 Specifications

Classic 10

Electronic Features	Control Panel	Digital
	Thermostat Control	Electronic
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	10,000 Btu/h
Electrical Characteristics	Voltage Requirement	1 Phase, 115 V
	Total Power Consumption	1.1 kW
	Current Consumption	10 amps
	Recommended Fuse Size	15 amps
	NEMA Plug Configuration	5-15
	Min. – Max. Voltage	105 – 125 V
Fans	Motor Output	0.15 kW
Evaporator	Fan Type	Centrifugal
	Max. Air Flow	265 CFM
	Max. External Static Pressure	0.33 IWG
Condenser	Fan Type	Centrifugal
	Max. Air Flow	740 CFM
	Max. External Static Pressure	0.13 IWG
Compressor	Type	Hermetic Rotary
	Output	0.7 kW
Refrigerant	Type / Pre-charged Amount	R-410A / 1.43 lb
Dimensions	W x D x H	19 x 26 x 41 in
Net Weight/Shipping Weight		156/194 lb
Power Cord	Gauge	14 AWG (3-core)
	Length	10 ft
Condensate Tank Capacity		5 gal
Operating Conditions	Min. – Max. @ 50% RH	70° – 105°F
Max. Duct Length	Per Cold Duct Hose	40 ft
	Hot Duct Hose	60 ft
Max. Sound Level	With Condenser Duct - High/Mid/Low	55 dB(A)
	Without Condenser Duct - High/Mid/Low	58 dB(A)

All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit MovinCool.com/warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.